

Low Light 8MP USB3.0 Camera Module Specifications



I. Main Parameters

Product Name	Low Light 8MP 4K USB3.0 Camera Module
Product Code	WN-L2309K357-V3.1 585
Module Size	38*38mm
Image Sensor	1/1.2-inch CMOS Sensor
Max. Resolution	3840H*2160V
Pixel Size	2.9*2.9μm
Output Format	MJPEG, YUY2, NV12, H264, H265
Field of View	125°
Digital Noise Reduction	Adaptive 2D-DNR and 3D-DNR
Lens	FEL:6.93mm F/NO:1.0 5G+4P IR 650NM
Focus Mode	Fixed Focus/ Manual Focus
Shutter Mode	Electronic Rolling Shutter
Dynamic Range	Support
Minimum Illumination	0.0001Lux
Output & Power Supply	High Speed USB3.0
Interface	USB3.0 USB2.0 HDMI
Controllable Parameters	Brightness, Contrast, Saturation, Hue, Gain, Sharpness, Gamma, White Balance, Backlight Contrast, Exposure
Supported OS	UVC-compliant, Plug and Play for Windows, Android, Linux, Mac OS, etc.
Connection Cable	Default 1.5 Meter USB Cable

2. Resolutions and Frame Rates

Formats	Resolutions	Frame Rates
MJPG	3840*2160(4K)	30FPS
	3264*2448(8MP)	30FPS
	2592*1944(5MP)	30FPS
	2560*1440(2K)	30FPS
	2048*1536(3MP)	30FPS
	1600*1200(2MP)	30FPS
	1920*1080 (1080P)	30FPS
	1280*720 (720P)	30FPS
	640*480 (VGA)	30FPS
YUY2	3840*2160(4K)	10FPS
	3264*2448(8MP)	10FPS
	2592*1944(5MP)	20FPS
	2560*1440(2K)	30FPS

	2048*1536(3MP)	30FPS
	1600*1200(2MP)	30FPS
	1920*1080 (1080P)	30FPS
	1280*720 (720P)	30FPS
	640*480 (VGA)	30FPS
NV12	3840*2160(4K)	10FPS
	3264*2448(8MP)	10FPS
	2592*1944(5MP)	20FPS
	2560*1440(2K)	30FPS
	2048*1536(3MP)	30FPS
	1600*1200(2MP)	30FPS
	1920*1080 (1080P)	30FPS
	1280*720 (720P)	30FPS
	640*480 (VGA)	30FPS
H.264	3840*2160(4K)	30FPS
	3264*2448(8MP)	30FPS
	2592*1944(5MP)	30FPS
	2560*1440(2K)	30FPS
	2048*1536(3MP)	30FPS
	1600*1200(2MP)	30FPS
	1920*1080 (1080P)	30FPS
	1280*720 (720P)	30FPS
	640*480 (VGA)	30FPS
H.265	3840*2160(4K)	30FPS
	3264*2448(8MP)	30FPS
	2592*1944(5MP)	30FPS
	2560*1440(2K)	30FPS
	2048*1536(3MP)	30FPS
	1600*1200(2MP)	30FPS
	1920*1080 (1080P)	30FPS
	1280*720 (720P)	30FPS
	640*480 (VGA)	30FPS

3. Working Conditions

Working Voltage	DC 5V
Working Current	600mA
Working Temperature	-10°C ~ 60°C
Storage Temperature	-20°C ~ 85°C
Humidity	80 ~85%

4. Shape and Dimensions (Unit: mm)

